


LIGHT TRANSPORTATION VEHICLES

APE TM Pick-Up

APE TM Panel Van

TECHNICAL SPECIFICATIONS

	APE TM petrol		APE TM diesel	
ENGINE	two strokes single-cylinder		4 strokes indirect injection	
DISPLACEMENT	218 cc		422 cc	
AMAX. CAPACITY	7 Kw at 4500 rpm		8,5 Kw at 4300 rpm	
IGNITION	electronic		-	
ELECTRIC SYSTEM	12V - 130 W genemotor		12V with 12V 330 W flywheel magneto alternator	
TRANSMISSION GEAR	4 gears plus reverse		4 gears plus reverse 5 gears plus reverse (steering wheel model)	
FRONT SUSPENSIONS	swinging arm with coil spring and hydraulic shock-absorber		swinging arm with coil spring and hydraulic shock absorber	
REAR SUSPENSIONS	independent with triangular swinging arms and hydraulic shock-absorber with rubber spring		independent with triangular swinging arms and hydraulic shock absorber with rubber spring	
BRAKES	double hydraulic circuit		double hydraulic circuit	
MAX. SPEED WITH LOAD	60 Kmph		63 Kmph	
CONSUMPTION with load at 40 Kmph	16.5 Km/lt		29 Km/lt	
TANK CAPACITY	15 litres		15 litres	
MAX. SLOPE GRADIENT (full load)	20%		20%	
TURNING CIRCLE	7 m		7 m	
PAYLOAD	over 700 Kg pick-up model		over 700 Kg pick-up model	
TYRES	handlebar version: 4.00 12C front 125 R12C rear	steering wheel model: 125 R12C	handlebar version: 4.00 12C front 125 R12C rear	steering wheel model: 125 R12C

DIMENSIONS

FRAME	PICK-UP	PICK-UP (LONG DECK)	TIPPER	PANEL VAN
petrol diesel		petrol diesel	petrol diesel	

A	3.150 3.210	3.175	3.390	3.225	3.335	3.210
B	1.480	1.480	1.500	1.530	1.480	
C	1.630	1.630	1.630	1.630	1.780	
D	-	1.480	1.470 1.494	1.520	1.460	
E	-	1.830	2.040	1.877	1.995	1.800

dimensions in mm

APE TM Pick-up is also available with tipper

